



## Smart Battery Chargers

**GPC-35-MAX / GPC-45-MAX / GPC-55-MAX  
GPC-75-MAX / GPC-100-MAX  
GPC-24-15 / GPC-24-25**

### Go Power!<sup>TM</sup> Smart Battery Chargers

#### Applications Include:

- RV's / Campers
- Long Haul Trucks
- Boats
- Mobile Offices
- Service Vehicles
- Scissor Lifts

SPECIFICATIONS*	GPC-35	GPC-45	GPC-55	GPC-75	GPC-100	GPC-24-15	GPC-24-25
DC Output Voltage (No Load) approx	13.6V (DC)	13.6V (DC)	13.6V (DC)	13.6V (DC)	13.6V (DC)	27.2 V (DC)	27.2 V (DC)
Output Voltage Tolerance (No Load)	+ / - 0.7%	+ / - 0.7%	+ / - 0.7%	+ / - 0.7%	+ / - 0.7%	+ / - 0.5%	+ / - 0.5%
Output Amperage, Max Continuous	32 Amps	45 Amps	55 Amps	75 Amps	100 Amps	15 Amps	25 Amps
Output Voltage (Full Load) approx	>13.4V (DC)	>13.4V (DC)	>13.4V (DC)	>13.4V (DC)	>13.4V (DC)	>27.0 V (DC)	>27.0 V (DC)
Maximum Power Output, Continuous	430 watts	600 watts	780 watts	1065 watts	1400 watts	400 watts	675 watts
Input Voltage Range	105-135AC	105-135AC	105-135AC	105-135AC	105-135AC	108-132 AC	108-132 AC
Input Voltage Frequency	47-63	47-63	47-63	47-63	47-63	47-63	47-63
Maximum AC Current @ 108Vac	10 Amps	10 Amps	12 Amps	12 Amps	17 Amps	7 Amps	12 Amps
Typical Efficiency	>85%	>85%	>85%	>85%	>85%	>80%	>80%
Max Inrush Current, Single Cycle	40 Amps	40 Amps	40 Amps	40 Amps	40 Amps	30 Amps	40 Amps
Short Circuit Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Overload Protection	>100%	>100%	>100%	>100%	>100%	>100%	>100%
Fan Control	Proportional	Proportional	Proportional	Proportional	Proportional	Proportional	Proportional
Thermal Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Working Temperature Range	0-45C°	0-45C°	0-45C°	0-45C°	0-45C°	0 - 40C°	0 - 40C°
Dimensions	7.5 x 10.5 x 3.45"	7.5 x 10.5 x 3.45"	7.5 x 10.5 x 3.45"	7.5 x 10.5 x 3.45"	7.5 x 10.5 x 3.45"	9.7" x 6.7" x 3.4"	9.7" x 6.7" x 3.4"
Weight	5.0 lbs	5.0 lbs	5.0 lbs	5.0 lbs	10.0 lbs	5.0lbs	5.0lbs

\* Specifications subject to change without notice

**The POWER to GO anywhere!**

www.gpelectric.com | 1.866.247.6527 | sales@gpelectric.com